

Initial maintenance of hardwax oil and UV oil finished floor (Right after installation /before use)

To ensure maximum protection and saturation of the oil finished floor, especially when the floor is used for heavy traffic or in a commercial environment, it is recommend to clean the surface with WOCA natural soap for medium and dark coloured floors, or with WOCA white soap for light and pale coloured floors, in order to add extra white pigments to preserve the light nuance.

WOCA - Natural Soap Natural/White

A purpose-made, quality soap, which due to its nourishing properties quickly closes the pores of the wood and protects against dirt and penetration of liquids. 'Natural Soap' cleans and nourishes the floor in one step. Ideal for all oiled, waxed or soaped surfaces.

Tools

Two plastic buckets, 'WOCA Sweep Mop', floor cloth or similar. After application, clean tools with water and soap.

Applying Natural Soap

1) 'Natural Soap' is shaken carefully before use.

2) 125ml 'Natural Soap' is mixed into 5litres of lukewarm water. It is recommended always to work with 2 buckets: one with soap water, and one with rinse water .Clean the floor with minimum quantity of water - leave soap water on floor briefly in order to dissolve dirt. Remove dirty soap water with a well wrung out mop or cloth, and rinse out in bucket with clean water.

3) Always wipe the floor with soap water with well wrung out mop or cloth in order to re-establish the protective Natural Soap film.

Tip: Very dirty floors may be cleaned with 'Wood Cleaner', and subsequently with 'Natural Soap'. Areas of oxidative oiled floor with heavy wear may be maintained with 'Maintenance Oil' after cleaning with 'Wood Cleaner'. Particularly difficult stains may be removed with 'Spot Removal'.